

UHF 6th Order (4+2)Dual Mode Reflective DTV/DVB-T Mask Filter

- **Thermally Adjusted**
- **DTV Mask Compliant**
- **3-1/8 EIA In and Out
Other Connectors Available**
- **Thermally Stable Invar
Available upon request**

Electrical Specifications

Filter Type	Band Pass Dual Mode
Order	6th
Frequency Range	470- 862 MHz
Impedance	50 Ohm
Maximum RMS Power	20kW(30kw Max- 4-1/16EIA)
Connectors	3-1/8 EIA(Male)
Channel Bandwidth	6 MHz (8MHz Optional)
VSWR	1.08:1
Insertion Loss	@ fc=.25dB
Frequency Response	6MHz Pass Band
fc± 4.0 MHz	≤5.9dB
fc± 4.5 MHz	≤11.6dB
fc± 5.0 MHz	≤18.0dB
fc± 5.5 MHz	≤25.0dB
fc± 6.0 MHz	≤30.0dB
fc± 9.0 MHz	≤60.0dB
Group Delay Variation	≤150 ns
Normal Operating Temp.	Ambient to 150°F (65°C)

Mechanical & Environmental Specifications

Dimensions -Typical @CH 33	16.5"Ø x 68" LG	
Materials	Outer Conductor	6061 Aluminum
	Finishing	Long Lasting Black Paint
	Hardware	Stainless Steel
Temperature Range	-10° to +50°C	

